


CoolSNAP^{EZ} Monochrome

1392 x 1040 imaging array | 6.45 x 6.45- μ m pixels



The CoolSNAP^{EZ} Monochrome camera from Photometrics® is a fast, high-resolution digital imaging system designed for low-light life sciences applications. This moderately cooled CCD camera system provides 12-bit digitization at 20 MHz. The fine pitch of the pixels is ideally matched to the resolution of optical microscopes. Megapixel resolution and small pixels allow imaging of very fine detail, yet the pixels can be easily binned to utilize the full dynamic range and increase signal-to-noise. New interline-transfer CCD technology provides high quantum efficiency, most notably in the near-infrared (NIR) portion of the spectrum.

Features	Benefits
20-MHz read-out	High-speed, high-sensitivity readout
1392 x 1040 imaging array 6.45 x 6.45- μ m pixels	Resolves fine detail Ideally matched to optical microscope
Interline-transfer, progressive-scan CCD	Electronic shuttering eliminates camera vibration and facilitates fast triggering
Flexible binning and readout	Increases signal-to-noise while increasing the frame rate
IEEE-1394a or PCI interface	High-bandwidth, uninterrupted data transfer with no dropped frames
12-bit digitization	Quantifies bright and dim signals in the same image
Thermoelectric cooling	Low dark current allows longer integration times
Enhanced quantum efficiency	Provides higher sensitivity than typical interline cameras (especially in the NIR)
C-mount	Easily attaches to microscopes, standard lenses, or optical equipment
Subcompact, fanless design	Low profile allows easy integration
Acquisition software	Captures, analyzes, and saves high-resolution images
PVCAM® Circular buffers Device sequencing IEEE-1394a compatibility PCI compatibility	Supported by numerous third-party software packages Real-time focus Precise integration with shutters, filter wheels, etc. Windows® 2000/XP Windows 2000/XP, Mac OS X, and SUSE™ Linux® 9.2 (kernel version 2.6)




		Region		
		1392 x 1040	512 x 512	256 x 256
Binning	1 x 1	10	20	36
	2 x 2	19	35	56
	3 x 3	27	46	69
	4 x 4	33	54	78
	8 x 8	50	74	97

(Frames per second)

Note: Frame rates are measured at 20 MHz with 0-millisecond exposure times.

Specifications

CCD image sensor	Sony® ICX285; interline-transfer, progressive-scan device with microlenses
CCD format	1392 x 1040 imaging array 6.45 x 6.45-µm pixels 8.98 x 6.71-mm imaging area (optically centered)
Grade	Sony Grade 0
System Gain	3 e-/ADU
Linear full well	12,300 e- (single pixel) 24,500 e- (2 x 2 binned pixel)
Read noise	≤8 e- rms @ 20 MHz
Nonlinearity	<1%
Digitizer type	12 bits @ 20 MHz
Frame readout	96 ms/frame
CCD temperature	5°C below ambient
Dark current	1 e-/p/s
Operating environment	15 to 30°C ambient, 0 to 80% relative humidity noncondensing
Dimensions	4.5" x 5.0" x 2.5" (1.9 lbs)
I/O	TTL output while exposing (BNC connector)



Note: Specifications are typical and subject to change.

CoolSNAP is a trademark of Roper Scientific, Inc. Photometrics, PVCAM, and Roper Scientific are registered trademarks of Roper Scientific, Inc. Linux is a registered trademark of Linus Torvalds. Mac OS is a trademark of Apple Computer, Inc., registered in the U.S. and other countries. Sony is a registered trademark of Sony Corporation. SUSE is a trademark of SUSE LINUX Products GmbH, a Novell business. Windows is a registered trademark of Microsoft Corporation in the United States and other countries. Other brand and product names are the trademarks or registered trademarks of their respective owners and manufacturers.

