

///MotionXtra® HG-SE

Redlake's *MotionXtra*® HG-SE high-speed CMOS camera combines ease-of-use and value for your high-speed motion application. The HG-SE offers maximum resolution of 1280 x 1024 at 500 fps, with frame rates up to 32,000 fps at reduced resolutions.

Specifically designed for rugged environments such as vehicle impact testing, the new innovative *MotionXtra* HG-SE high-speed digital camera architecture puts it in a class by itself. Small and lightweight, the HG-SE features stand-alone battery operation and robust high-G construction.

The *MotionXtra* HG-SE features built-in image memory for storing the recorded high-speed sequence for playback, editing or downloading to the PC's hard disk. Just choose which image memory option best fits your application requirements. Flexible triggering lets you create the best pre- and post- event trigger settings enabling you to capture perfect images every time.

The HG-SE's internal battery provides up to 30 minutes of standalone operation and up to 4 hours in stand-by mode. Since the HG-SE is self-contained (no bulky processor or tethered cables to contend with) the only connection required is a trigger cable.

Thanks to its intuitive and reliable "point and click" Windows control software, the *MotionXtra* HG-SE is exceptionally simple to set up and operate. Advanced features are included in the standard Image Studio software. The camera is interfaced to your PC via Firewire (IEEE-1394).

Small and Lightweight High-G Camera



S N A P S H O T

- **Speeds of 500 fps at a full resolution of 1280 x 1024, and up to 32,000 fps at reduced resolutions**
- **Small (97 x 71 x 71mm) and lightweight (under 2 pounds/1 kg)**
- **Internal battery for stand-alone use**
- **Firewire interface for easy set-up and fast image downloading**
- **Rugged design to withstand up to 100G in any axis**

A P P L I C A T I O N S

- **Vehicle impact testing (VIT)**
- **On-board vehicle safety component testing**
- **Military vehicle and ordinance testing**
- **Remote tests**



REDLAKE

Web www.redlake.com

Email sales@redlake.com

///MotionXtra® HG-SE

PERFORMANCE SPECIFICATIONS

Resolution	1280 x 1024 pixel (8-bit monochrome or 24-bit color)
Speed	62 to 32,000 frames per second
Exposure Rates	Global Electronic Shutter from 4 µsec to 1/frame rate
File Formats	Raw data (Bayer), AVI, BMP, GIF, JPEG, MPEG, TIFF
Frame Storage	1024 frames at 1280 x 1024 (2 seconds record time at 500fps)
Memory Upgrade	2048 frames at 1280 x 1024 (4 seconds record time at 500fps)
Power	Power via FireWire or 12 vdc power supply
Software	Image Studio for Windows XP or 2000
Standard Lenses	C-mount (1" format); includes F-mount adapter; other adapters optional
Camera Size	3.9" x 2.9" x 2.9" (97 x 71 x 71 mm)
Camera Weight (incl. Standard Battery)	1.87 lb (0.85 kg)
Battery Capacity	Recording mode: 30 min.; standby mode: 4 hours

Note: Specs are subject to change at any time

MotionXtra HG-SE 1.3 GB Memory - Sample Frame Rates			
Resolution	Frame Rate	Number of Frames	Duration
1280 x 1024	500 fps	1024	2 seconds
640 x 512	1000 fps	4096	4 seconds
320 x 256	2000 fps	16,384	8 seconds
320 x 128	4000 fps	32,768	8 seconds
160 x 64	8000 fps	65,536	16 seconds
160 x 32	16,000 fps	262,144	16 seconds
160 x 16	32,000 fps	524,288	16 seconds

MotionXtra HG-SE 2.6 GB Memory - Sample Frame Rates			
Resolution	Frame Rate	Number of Frames	Duration
1280 x 1024	500 fps	2048	4 seconds
640 x 512	1000 fps	8192	8 seconds
320 x 256	2000 fps	32,768	16 seconds
320 x 128	4000 fps	65,536	16 seconds
160 x 64	8000 fps	262,144	32 seconds
160 x 32	16,000 fps	524,288	32 seconds
160 x 16	32,000 fps	1,048,576	32 seconds

Worldwide Sales and Support

Americas
tel: +1-800-462-4307
tel: +1-858-481-8182
sales@redlake.com

Asia Pacific
tel: +65-6293-4758
salesASPAC@redlake.com

Japan
tel: +81-3-5639-2770
salesJapan@redlake.com

Europe, Africa and Middle East
tel: +31-347-324989
salesEurope@redlake.com

Copyright © 2004 Redlake, MASD, LLC

All Rights Reserved

HG-SE 06/05

